

DC CHAIN DRIVE GARAGE DOOR OPENER

Trusted reliability and quiet operation.



WARRANTY

4-YEAR
Motor

1-YEAR
Parts and
Accessories

RELIABLE

P3
MOTORS®

CUSTOMIZED DC MOTOR IS PURPOSEFULLY DESIGNED AND BUILT TO LAST.

CHAIN DRIVE SYSTEM FOR STEADY PERFORMANCE AND INDUSTRIAL STRENGTH.

SOFT START/STOP FOR SMOOTH OPERATION.

SMART

myQ

MONITOR AND CONTROL THE OPENER FROM ANYWHERE USING MOBILE DEVICES.

FREE MyQ® MOBILE APP SO USERS KNOW THEIR HOME IS SECURE.

REAL-TIME ALERTS INDICATE THE STATUS OF THE GARAGE DOOR VIA EMAIL OR PUSH NOTIFICATIONS.

SECURE

Security+ 2.0®

SAFEGUARDS GARAGE ACCESS BY SENDING A NEW CODE WITH EVERY CLICK.

POSILOCK® ELECTRONICALLY PROTECTS AGAINST FORCED OPENINGS.

ALERT-2-CLOSE SIGNALS WHEN A DOOR IS BEING CLOSED BY MyQ.

THE PROTECTOR SYSTEM® INVISIBLE LIGHT BEAM AUTO-REVERSES THE DOOR IF THERE IS AN OBSTRUCTION.

INCLUDED ACCESSORIES:

Multi-function Control Panel®

Turns on garage door opener lights from inside the garage.



6080960

882RCGD

3-Button Remote Control

Operates up to 3 openers or MyQ Light Accessories.



2220178

893RCGX

POWERFUL ADD-ONS:

Mini Universal Remote Control

Compact and portable to provide quick, easy garage access.



2220185

374UT

Internet Gateway

Connects the opener to the Internet, enabling smartphone control.



2220170

828LM

Remote Light Control

Enables home lighting control through a garage remote or a smartphone.



2220174

825LM

Remote Light Switch

Replaces an existing wall switch to enable home lighting control with a garage remote or a smartphone.



2220183

823LM

Garage Door and Gate Monitor

Monitors and closes up to 4 garage doors from any room in the house.



2220175

829LM

MASTERFUL ENGINEERING.

MOTOR

- 12VDC
- 53 RPM
- Automatic Thermal Protection
- Permanent Lubrication

POWER

- 120VAC
- 60 Hz Voltage
- 2.7A Current Rating
- UL Listed
- 4' Power Cord (3-Prong)

MECHANICS

- **Steel Chassis, T-Rail and Trolley**
- **Full Chain Drive Mechanism** (63:1 Gear Reduction and Adjustable Door Arm)
- **Auto-Force** Adjustment for Changing Weather and Environmental Conditions
- **Electronic Limits** for Easy Setup
- **DC Logic Board** with Built-In Surge Suppressor

7.67"



15.2"

10.5"

DIMENSIONS

Rail Options	7'	8'	10'
Installed Length	128"	140"	164"
Max. Opening	7'6"	8'6"	10'6"

Headroom Clearance Required: 2"

8"

Per second for door to move upward

SPEED

6.5"

Per second for door to move downward

STANDARD SPECS.

SECURITY

SECURITY+ 2.0® RADIO CONTROLS

3-Button Remote Control

Operating Range: ~200'

Operating Temperature: -40°F to 150°F
Frequency:

- Remote Control: 310, 315 and 390 MHz Tri-Band
- Garage Door Opener: Frequency Agile on 310, 315 and 390 MHz
- Security+ 2.0 Anti-Burglary Coding

SECURITY+ 2.0 ENCRYPTED CONTROLS

- Multi-Function Control Panel® (882LMW)
- Program Remote Controls
- Maintenance Alert System

SMART

MyQ® RADIO

902-928 MHz

50-Channel FHSS

(Frequency Hopping Spread Spectrum)

- Provides 2-way communication from garage door opener and MyQ Accessories.
- Enables monitoring and control of garage door openers and lighting controls via smartphone, tablet or computer.*

*Requires Internet Gateway (828LM) 2220170

HOMELINK® COMPATIBLE (VERSION 4.0 OR HIGHER*)

*May require an external adapter depending on the model and year of your vehicle. Visit HomeLink.com for additional information.

ELECTRICAL

LIGHTING



- 1 100-Watt Lightbulb
- Adjustable Time, Solid-State Delay
- Enhanced CFL (Compact Fluorescent) Compatible, Max. 27 Watts

ENERGY EFFICIENCY

- Approximately 1-Watt Power in Standby Mode*
- *Occurs at Down Limit When Opener's Lights Turn Off

SHIPPING.

SHIPPING WEIGHT (in lbs.)

18
HEAD

20
RAIL (X')

CARTONS (2)

CARTON 1: 20" x 12" x 10"

- Multi-Function Control Panel (882LMW)
- 3-Button Remote Control (893LM)
- Garage Door Opener Head Sergeant™ II
- The Protector System® Safety Reversing Sensors

CARTON 2: 10'4" x 5" x 5"

- Assembled Solid-Steel Chain T-Rail

CONVENIENCE AND SAFETY.

- Alert-2-Close Unattended Close Operation*
- Hands-Free Work Lights On
- Emergency/Quick Release
- Automatic Trolley Reconnect
- Ventilation/Pet Opening
- Down Safety Reverse
- Up Safety Stop
- Safety Beam Break Turns Lights On
- Maintenance Alert System

*Unattended Operation functionality cannot be utilized when opener is installed on a one-piece door.



HomeLink® and the HomeLink House® logo are registered trademarks of Genex Corporation

Note: to reduce the risk of injury to persons, when the Internet Gateway is used with garage door openers, the operator must be installed with sectional doors.