



commercial sectional doors



TriCore STANDARD, white, with full-view windows



AlumaView STANDARD, bronze-anodized



SteelForm STANDARD, white, with oval windows

TRICORE™
SECTIONAL THERMAL DOORS

THERMASEAL™
SECTIONAL THERMAL DOORS

STEELFORM™
SECTIONAL RIBBED DOORS

ALUMAVIEW™
SECTIONAL RAIL & STILE DOORS

STYLEFORM™
SECTIONAL RAISED PANEL DOORS

OVER HALF A CENTURY OF WORKING WITH ARCHITECTS AND SPECIFIERS

Professionals like you have counted on Raynor commercial doors and operators for over 50 years. We pride ourselves on fast, individualized product information and service, and we can provide product information via fax or next-day delivery. For your convenience, our commercial specifications and drawings can be downloaded from our website and are available on CD-ROM. Raynor Field Representatives are also available to assist with product specifications as well as provide technical training. Our exclusive, professional network of over 600 dealers and their commitment to customer service has helped make us recognized experts in the industry for over 50 years. Count on your Raynor Dealer for the proper selection and expert installation you deserve.

NEW! Every Raynor Commercial Sectional door is available with our optional white, powder-coated hardware system.



TRICORE™
SECTIONAL THERMAL DOORS

With a proven track record for thermal efficiency and extreme durability, 3"-thick TriCore is simply the best commercial sectional door you can specify. With expanded polystyrene insulation bonded between two steel skins, TriCore has an exceptional R-value of 16.05. When you want the best, specify TriCore.

Series MODEL	Max. Opening Width	Max. Opening Height	Construction	Surface Texture	Section Thickness	Exterior/Interior Steel Thickness	End Stile Steel Thickness	Insulation (R-Value)	Thermal Break	Exterior Colors	Section Warranty
TriCore OPTIMA (TC-20)	32'	24'	Steel Sandwich	Smooth	3"	20-Gauge 25-Gauge (Optional 20-Gauge Interior)	14-Gauge	Polystyrene (16.05)	Yes	White	1-Year (Rust) 10-Year (Delamination)
TriCore STANDARD (TC)	32'	24'	Steel Sandwich	Stucco	3"	25-Gauge 25-Gauge	14-Gauge	Polystyrene (16.05)	Yes	White, Frost White*, Dark Brown*, Sepia*, Beige*	1-Year (Rust) 10-Year (Delamination)

WARRANTY TriCore door sections carry an exclusive 10-year delamination warranty (of the steel door skins from the insulation) and a 20-year insulation warranty in addition to the standard 1-year limited warranty against any rust on all other door components. See your local Raynor Dealer for complete details.



THERMASEAL™
SECTIONAL THERMAL DOORS

ThermaSeal doors are both durable and energy efficient. An exclusive process fills 100% of the door's interior with energy-saving polyurethane insulation to deliver exceptional R-values of 16.4 for the 1-3/4"-thick model and 14.5 for the 1-1/2" door.

Series MODEL	Max. Opening Width	Max. Opening Height	Construction	Surface Texture	Section Thickness	Exterior/Interior Steel Thickness	End Stile Steel Thickness	Insulation (R-Value)	Thermal Break	Exterior Colors	Section Warranty
ThermaSeal STANDARD	28'	20'	Steel Sandwich	Stucco	1 3/4"	25-Gauge 26-Gauge	16-Gauge	Polyurethane Foam (16.4)	Yes	White, Dark Brown*	1-Year (Rust) 10-Year (Delamination)
ThermaSeal BASIC	16'	16'	Steel Sandwich	Stucco	1 1/2"	26-Gauge 26-Gauge	16-Gauge	Polyurethane Foam (14.5)	Yes	White	1-Year (Rust) 10-Year (Delamination)

WARRANTY ThermaSeal door sections carry a 1-year limited warranty against any rust and a 10-year limited warranty against delamination (of the steel door skins from the insulating foam). Hardware and springs are warranted for 1-year against defects in materials and workmanship. See your local Raynor Dealer for complete details.

*Features the Kynar™ paint process, which provides extended UV protection against fading



STEELFORM™

SECTIONAL RIBBED DOORS



Rugged SteelForm doors are a standard choice for commercial and industrial garage door needs. Constructed from a single layer of steel with optional windows and insulation, SteelForm sections are a full 2" thick and made of hot-dipped, galvanized steel for maximum rust resistance.

Series MODEL	Exterior Steel Thickness	Max. Opening Width	Max. Opening Height	Construction	Surface Texture	Section Thickness	End/Center Stile Steel Thickness	Optional Insulation (R-Value)	Exterior Colors	Section Warranty
SteelForm OPTIMA (S-16)	16-Gauge	24'	24'	Steel Pan	Smooth (Flush)	2"	13-Gauge/16-Gauge	Polystyrene (7.70) Fiberglass (7.57)	White	1-Year (Rust)
SteelForm STANDARD (S-20, S-24)	20-Gauge	32'	24'	Steel Pan	Smooth (Ribbed)	2"	16 or 13-Gauge/16-Gauge	Polystyrene (7.70) Fiberglass (7.57)	White Frost White*, Dark Brown*, Sepia*, Beige*	1-Year (Rust)
	24-Gauge	24'	24'							
SteelForm BASIC (S-24C)	24-Gauge Nominal	16'	16'	Steel Pan	Smooth (Ribbed)	2"	16-Gauge/16-Gauge	Polystyrene (7.70) Fiberglass (7.57)	White	1-Year (Rust)

WARRANTY SteelForm doors carry a 1-year limited warranty against any rust. See your local Raynor Dealer for complete details.



ALUMAVIEW™

SECTIONAL RAIL & STILE DOORS

AlumaView has long been the standard fixture for facilities that require a dependable, attractive door with maximum visibility. With an anodized finish in an extruded aluminum frame, AlumaView is available in either 1-3/4" or 2" thick sections. AlumaView is also available in any of 187 ArmorBrite™ powder-coated colors or in special anodized finishes.

Series MODEL	Max. Opening Width	Max. Opening Height	Overall Section Thickness	End Stile Width	Center Stile Width	Colors	Warranty
AlumaView OPTIMA (HL)	24'	24'	2"	3 1/4" or 6 1/4"	3 5/8"	Clear-Anodized Finish or 187 ArmorBrite™ Colors	1-Year
AlumaView STANDARD (L)	14'	14'	1 3/4"	2 5/8"	7 1/16"	Clear-Anodized Finish or 187 ArmorBrite™ Colors	1-Year

WARRANTY AlumaView doors carry a 1-year limited warranty. See your local Raynor Dealer for complete details.



STYLEFORM™


SECTIONAL RAISED PANEL DOORS

When exterior appearance is a primary consideration, choose a classic, raised panel door from our attractive StyleForm series.

Series MODEL	Max. Opening Width	Max. Opening Height	Construction	Surface Texture	Section Thickness	End/Center Stile Steel Thickness	Insulation (R-Value)	Thermal Break	Exterior Colors	Section Warranty
StyleForm OPTIMA (Commercial Decade ShowCase)	18'	14'	Steel Sandwich	Raised-Panel/Flush (Woodgrain)	2"	18-Gauge/ N/A	Polystyrene (10.25)	Yes	White, Almond, ClayTone, Brown, Frost White*, Beige*, Sepia*, BronzeTone	1-Year (Rust) 5-Year (Delamination)
StyleForm STANDARD (Commercial Decade II)	18'	14'	Steel Pan (24-Gauge)	Raised-Panel (Woodgrain)	2"	18-Gauge/18-Gauge	Polystyrene-Optional (5.0)	No	White, Almond, ClayTone, Brown, BronzeTone	1-Year (Rust)
StyleForm BASIC (Commercial Classic)	14'	14'	Steel Pan	Raised-Panel (Pebblegrain)	2"	18-Gauge/18-Gauge	Polystyrene-Optional (5.0)	No	White, Almond, ClayTone, Brown	1-Year (Rust)

WARRANTY StyleForm door sections carry a 1-year limited warranty against any rust and a 5-year limited warranty against delamination of the steel door skins from the insulating foam. See your local Raynor Dealer for complete details.

*Features the Kynar™ paint process, which provides extended UV protection against fading



POWERHOIST™

COMMERCIAL OPERATORS

Raynor offers a full line of rugged PowerHoist operators for both trolley and jackshaft operation.

Series MODEL	Operation Mode	Duty Cycle	Drive	Environmental Options (NEMA)	Motor	Logic	Power	Brake	Hand Chain (Jackshaft Only)	Warranty
PowerHoist OPTIMA	Jackshaft or Trolley	30/hr	Gear	1-Standard 4-Water 7-Explosion 9-Explosion 12-Dust	Continuous-Duty 1/2-2hp O.D.P.-Standard T.E.F.C.-Optional	Relay	115/230v, 1-Phase 230/460v, 3-Phase	Jackshaft-Standard Trolley-Standard	Standard	1-Year
PowerHoist STANDARD	Jackshaft or Trolley	30/hr	Belt	1-Standard 12-Dust	Continuous-Duty 1/3-3/4hp O.D.P.-Standard T.E.F.C.-Optional	Relay	115/230v, 1-Phase 230/460v, 3-Phase	Jackshaft-Standard Trolley-Optional*	Optional	1-Year
PowerHoist BASIC	Jackshaft or Trolley	10/hr	Belt	1-Standard	Intermittent-Duty 1/2hp	Solid State or Relay	115v, 1-Phase	Jackshaft-Standard Trolley-Optional	Optional	1-Year Solid State 2-Year Relay
PowerHoist SELECT	Trolley	10/hr	Gear/Chain	1-Standard	Intermittent-Duty 1/2hp	Solid State	115v, 1-Phase	Gear Reduction	None	1-Year

*Standard on 3/4hp



Need AIA credits? Raynor provides courses covering a variety of door subjects. Call 1-800-4-RAYNOR for more information.

Raynor also offers a complete line of commercial rolling and fire doors, as well as traffic doors.

CALL
1-800-4-RAYNOR

CLICK
www.raynor.com

FAX
1-815-288-7142



Raynor Worldwide P.O. Box 448, 1101 East River Road, Dixon, IL 61021



This information was as complete and factual as possible at the time it was printed. We do, however, reserve the right to make changes in product specifications and availability without notice. Features and options may be different in countries other than the United States. Product colors have been reproduced as well as possible with present commercial printing processes. For absolute accuracy in color matching, use actual product samples.